

EO150

SPECIFICATIONS

EO150 Unit	10-UFF-0712
Fan motor rating	1 kW
Pump motor rating, kW	0.6 kW
Current consumption,	12 amps
Specified voltage	230 AC
Frequency	60 Hz
Power cable length	13 ft. / 4 m
Fan starter	DIRECT
Emergency stop	YES
Control panel buttons	Pump START/STOP Fan START/STOP (option) Turn ON/OFF
Weight	240 lbs. / 110 kg
Length	48" / 1.2 m
Width	30" / .75 m
Height	45" / 1 m
Elevation, HAND	20° to 60°
Throw (up to)	50 ft. / 15 m
Water connection	Thread 3/4" BSP (DN20)
Required in pressure	30-145 psi / 2-10 bar
Working pressure (at the nozzle)	1450 psi / 100 bar
Filtration system	60 microns
Wheel set	YES



Water Flow

Nozzle configuration - 2 clusters of 3 nozzles
Flow all nozzles (at 1400 psi) 2 l/min (1/2 gal/min)

Turning 20-40

Turning Electrical (automatic oscillation)
Turning area Center of turning area fixed
Turning area setting 20° or 40°

Gauges

0-40 bar gauge after filter, before pump
0-160 bar gauge after pump (nozzle pressure)

Valves

Possible to open/close water supply by hand
Hoses after pump certified for 100 bar

Ecolo Odor Control Technologies Inc.

59 Penn Drive, Toronto, ON,
Canada, M9L 2A6
(800) 667-6355 | (416) 740-3900
Fax (416) 740-3800



info@ecolo.com | www.ecolo.com

10770 Moss Ridge Road
Houston, TX 77043-1175
Tel (713) 357-6295
Fax (713) 490-1487