

E150T

SPECIFICATIONS

Ecolo E150T	10-ADC-E150-T
Fan motor rating	1 kW
Pump motor rating, kW	0.6 kW
Current consumption,	12 amps
Specified voltage	230 AC
Frequency	60 Hz
Power cable length	13 ft. / 4 m
Fan starter	DIRECT
Emergency stop	YES
Control panel buttons	Pump START/STOP Fan START/STOP (option) Turn ON/OFF
Weight	262 lbs. / 120 kg
Length	24" / .6 m
Width	30" / .75 m
Height	69" / 1.67 m
Elevation, HAND	20° to 60°
Throw (up to)	50 ft. / 15 m
Water connection	Thread 3/4" NPT
Required in pressure	30-145 psi / 2-10 bar
Working pressure (at the nozzle)	1000 psi / 69 bar
Filtration system	60 microns

Options:
Electrical 220 VAC, 50 Hz
Injector pump for concentrates



Flow

Nozzle configuration - 2 clusters of 3 nozzles
Odor control unit 2 L/min (.53 gal/min) w/injector
Dust control unit 4 L/min (1.06 gal/min) no injector

Turning 20-40

Turning Electrical (automatic oscillation)
Turning area Center of turning area fixed
Turning area setting 20° or 40°

Gauges

0-40 bar gauge after filter, before pump
0-160 bar gauge after pump (nozzle pressure)

Valves

Possible to open/close water supply by hand
Hoses after pump certified for 100 bar

Corporate Head Office

59 Penn Drive,
Toronto, Ontario M9L 2A6
Tel: (416) 740-3900
Toll Free: 1 (800) 667-6355
Fax: (416) 740-3800

Ecolo Odor Control Technologies Inc.



info@ecolo.com | www.ecolo.com

Sales & Distribution Center

5829 W Sam Houston Pkwy N.,
Suite 610, Houston, Texas 77041
Tel: (713) 357-6295
Toll Free: 1 (800) 667-6355
Fax: (713) 490-1487