

E300

SPECIFICATIONS

Part number	10-ADC-E300
Fan motor rating	5.5 kW
Pump motor rating	3.0 kW
Current consumption, max	18 Amps
Specified voltage	480 VAC, 3 Ph, 60 Hz
Frequency	L1-L2-L3-N
Power cable length	98 ft. / 30 m
Fan starter	SOFTSTARTER
Emergency stop	YES
Control panel switches	Fan Start and Stop Tilt up/down, Turn left/right Turn auto on/off, Turn area setting
*Optional voltage	400 (50 Hz) or 600 VAC



Weight	560 lbs / 435 kg
Length	57 " / 1.45 m
Width	51" / 1.3 m
Height	75" / 1.9 m
Elevation, ELECTRIC	-10° to +50°
Turning, ELECTRIC	Automatic oscillation
Turning area	All around, no mechanical limit
Turning area setting	15° or 30° or 60°
Throw (up to)	100 ft. / 30 m
Water connection	Thread 1" NPT
Water swivel	YES
Pressure gauges	Before filter, after filter, nozzle pressure
Required inlet pressure	30 - 80 psi / 2 - 8 bar

STANDARD EQUIPMENT

- Remote control
- Booster pump 7-10 bar
- Water swivel
- Automatic water inlet valve
- Auto water drain at shut down
- Pump run dry protection
- Filter system-500 micron
- Automatic turning system
- Hose and cable holder

OPTIONS

- Wheel set with hitch
- Dosing pump for additives
- Winter kit



HAND HELD REMOTE CONTROL

WIRELESS. Range 330 ft. at free line of sight.
 Functions: Start/Stop pump and fan, tilt up / down,
 turn left / right, turn auto on/off, emergency stop.

Corporate Head Office

59 Penn Drive,
 Toronto, Ontario M9L 2A6
 Tel: (416) 740-3900
 Toll Free: 1 (800) 667-6355
 Fax: (416) 740-3800

Ecolo Odor Control Technologies Inc.



info@ecolo.com | www.ecolo.com

Sales & Distribution Center

5829 W Sam Houston Pkwy N.,
 Suite 610, Houston, Texas 77041
 Tel: (713) 357-6295
 Toll Free: 1 (800) 667-6355
 Fax: (713) 490-1487