



E400 UNIT

OUTDOOR ODOR & DUST CONTROL



E400

SPECIFICATIONS

Ecolo E400	40F-480-3
Fan motor rating	11 kW
Pump motor rating	4 kW
Current consumption, max	28 A
Specified voltage	480VAC-3Phase
Frequency	L1-L2-L3-N
Power cable length	98 ft. / 30 m
Fan starter	SOFTSTARTER
Emergency stop	YES
Control panel	Buttons for machine Start and Stop Tilt up/down, Turn left/right Turn auto on/off, Turn area setting
*Optional voltage	400 or 600VAC-3Phase

Weight	1025 lbs / 465 kg
Length	57" / 1.45 m
Width	51" / 1.3 m
Height	75" / 1.9 m
Elevation, ELECTRIC	-10° to +50°
Turning, ELECTRIC	Automatic oscillation
Turning area	All around, no mechanical limit
Turning area setting	15° or 30° or 60°
Throw (up to)	130 ft. / 40 m
Throw (70% of water volume)	30- 115 ft / 9 - 35 m
Water connection	Thread 1" NPT or BSP (DN25)
Water swivel	YES
Pressure gauges	Before filter, after filter, nozzle pressure
Water filter	500 microns

Required inlet pressure	30 - 145 psi / 2-10 bar
	Pump to boost the water as standard equipment. Water drain (automatic valves installed at pump & filter)
Pressure guard	Cuts the pump if water supply is broken. Setting 4 - 20 psi / 2 - 10 bar
Nozzles	6 + 14
Maximum flow	14.5-19 gal/min 55-73 l/min
Flow minimum	4-4.8 gal/min 15-18 l/min
	Kit for winter operation available



Hand held remote control. WIRELESS. Range 330 ft. at free line of sight.
Functions: Start/Stop pump and fan, tilt up / down, turn left / right, turn auto on/off, emergency stop.
Water valve. Automatically opens/closes water supply at machine start.

Corporate Head Office

59 Penn Drive,
Toronto, Ontario M9L 2A6
Tel: (416) 740-3900
Toll Free: 1 (800) 667-6355
Fax: (416) 740-3800

Ecolo Odor Control Technologies Inc.



info@ecolo.com | www.ecolo.com

Sales & Distribution Center

5829 W Sam Houston Pkwy N.,
Suite 610, Houston, Texas 77041
Tel: (713) 357-6295
Toll Free: 1 (800) 667-6355
Fax: (713) 490-1487